

THEMETRAX:RIDE – BETA (subject to change)

Features

- AES67
- Playback Channels: 96
 - 96x mono files
 - 48x stereo files
 - 1x 96 track wav
 - Unrestricted Polyphony
- Output Channels: 16
- 2x Live inputs with DSP
- 96(+2)x16 matrix
- Channel ducking
- Automatic file format conversion
- OSC, STRING & RS232 API
- Triggerable Scripts
- 3rd Party Control (UDP & TCP)
- Artnet Recording
- 24 x 24 Artnet Universes
- LTC and Script Sync
- GPS Clock & Geolocation triggers

Certifications

- CE
- FCC
- UL
- CCC
- BSMI

Physical

- Dimensions (W x D x H) 150 x 105 x 38 (5.9" x 4.2" x 1.5")
- Weight (Net): 0.8 kg (1.8 lb)

Power

- Operating range: 10~36 VDC

- Power Consumption: 19W (Typical), 60W (Max)

Connectors

- Remote On/Off
- GPIO: 8
- 2x RS232
- 2x LAN (AES67, ArtNet, & Control selectable)

Environmental

- Operating Temperature -20 ~ 60°C/-4 ~ 140°F with 0.7m/s airflow
- Storage Temperature - 40 ~ 85°C/-40 ~ 185°F
- Relative Humidity Operating, 95% RH @ 40°C, Non-Condensing
- Non-Operating, 95% RH @ 60°C, Non-Condensing
- Shock Protection Operating, IEC 60068-2-27, 50G, half sine, 11ms
- Vibration Protection Operating, IEC 60068-2-64, 2Grms, random, 5 ~ 500Hz, 1hr/axis (SSD)
- Ingress Protection IP40

Optional Extras

- Cable locking kit
- DIN rail mounting kit
- 100-240VAC PSU

V0.5.77

Unit: mm

